

PERIFERNA PUMPA

0,75 kW

Professional



TEHNIČKE KARAKTERISTIKE :

- Max. temperatura pumpanog medija 40 °C
- Zaštita motora IP44
- Izolacija: Class F
- Sa ugrađenom termičkom zaštitom
- Max. usisna visina do cca 8 m (vertikalno)
- Max. radni tlak u zatvorenom sistemu : 8 bara
- Max. udio pijeska : 0,15% >>> 150 g/m3
- Motori s mogućnošću premotavanja
- Priključak na usisu : unutarnji navoj 1" (DN 25 mm)
- Priključak na izlazu : unutarnji navoj 1" (DN 25 mm)
- Vrsta pumpe : periferne



MATERIJALI IZRADE KPL. PUMPE :

- Tijelo pumpe: Sivi ljev
- Kućište motora: Legura aluminija
- Sa mehaničkom brtvom
- Osovina : Inox
- Rotor pumpe (lopatica) : Mesing
- zvijezdastog oblika

UPOTREBA :

- snadbjevanje domaćinstava te manjih industrijskih postrojenja pitkom i potrošnom vodom kod hidropak i hidrofor sistema kao i za navodnjavanje vrtova. Može da crpi vodu iz bušenih ili kopanih bunara kao iz rezervoara ili cisterni. Također se koristi za sve ostale kućne te industrijske potrebe gdje zadovoljavaju navedene tehn. karakteristike te materijali izrade .






PERFORMANSE

n= 2900 1/min

TIP PUMPE		P2		P1		AMPERA		Protok Q (m ³ /h - l/min)									
1~ 230 V - 50 Hz						1~		0.3	0.6	1.2	1.8	2.4	3				
						5	10	20	30	40	50						
						Pritisak H (m)											
		(HP)	(kW)			1x230V 50Hz											
PERIFERNA	0,75 kW	1	0.74	1.11		5.2		-	56	48	39	31	18				

*** Napomena 10 m = 1 bar



TIP PUMPE	DIMENZIJE													Kg
	A	B	C	D	E	F	H1	H2	DNA	DNM	I	L	M	
0,75 kW	71.5	50	290	135	112	172	75	179	1"G	1"G	310	185	195	9.5