

GLAVNE KARAKTERISTIKE I DIMENZIJE SPOJKI

veličina spojke	N n	K	Maksimalni dozvoljeni broj okretaja		PROVRTI d_1 i d_2					PROMJERI		DUŽINE			VIJENAC		demon- t. m- jere	TEŽINA kg	ZAMAŠNI MOMENT		
					Najmanji provrti		Normalni provrti	Maksimalni provrti													
			normalni min-1	povišeni min-1	d_1 mm	d_2 mm	d_1 i d_2 mm	d_1 mm	d_2 mm	D_1 mm	D_2 mm	l mm	L mm	c mm	h mm	g mm			a mm	Poz. 1 kgm ²	Poz. 2 kgm ²
ES 1	0,004		5600	6000	10	10	10, 14, 16, 18, 20	20	25	90		30	62	2	30		30	2	0,005	0,0037	0,0087
ES 2	0,008		5000	6000	12	12	12, 16, 20, 25	25	30	100		35	72	2	30		30	2,5	0,007	0,0072	0,0142
ES 3	0,012		4500	6000	16	16	16, 20, 25 28, 30	30	40	115		40	82	2	35		30	3,7	0,008	0,0158	0,0236
ES 4	0,024		4000	6000	20	20	20, 25, 30, 35, 38, 40	40	50	130		50	102	2	35		30	5	0,0226	0,026	0,0486
ES 5	0,045		3600	5600	20	25	25, 30, 35, 40, 45, 50	50	60	160		60	122	2	40		25	9	0,045	0,068	0,113
ES 6	0,075		3000	5000	25	30	30, 35, 40, 45, 50, 55, 60	65	75	190		75	152	2	40		25	15	0,096	0,150	0,246
ES 7	0,14		2650	4500	30	35	35, 40, 45, 50, 55, 60, 70	75	90	225	210	90	183	3	50	25	30	25	0,264	0,309	0,573
ES 8	0,22		2250	4000	35	40	40, 50, 60, 70, 80, 90	90	100	270	255	100	203	3	60	25	35	40	0,565	0,70	1,165
ES 9	0,30		2000	3600	40	45	50, 60, 70, 80, 90, 100	100	110	300	280	120	244	4	60	35	35	58	0,90	1,30	2,20
ES 10	0,42		1800	3300	45	50	50, 60, 70, 80, 90, 100, 110	110	125	340	320	140	284	4	70	35	35	83	1,75	2,10	3,85
ES 11	0,60		1650	3000	55	60	60, 70, 80, 90, 100, 110, 125	125	140	380	345	160	324	4	70	35	35	102	3,00	3,20	6,20
ES 12	1,0		1500	2800	65	70	70, 80, 99, 100, 110, 125, 140	140	160	440	400	180	364	4	85	45	40	163	5,6	8,10	13,70
ES 13	1,4		1250	2500	75	80	80,90, 100, 110, 125, 140, 160	160	180	500	460	200	404	4	85	45	40	221	10,9	14,0	24,90
ES 14	2,3		1120	2250	85	90	90, 100, 110, 125, 140, 160, 180	180	200	560	505	220	444	4	100	50	40	326	19,0	26,0	45,0
ES 15	3,7		1000	2000	95	100	100, 110, 125, 140, 160, 180, 200	200	220	640	585	250	504	4	100	50	40	469	33,2	44,0	77,2
ES 16	6,8		850	1750	110	110	110, 125, 140, 160, 180, 200, 220	220	250	750	685	280	565	5	120	60	40	658	73	92	165,0

MAKSIMALNI PROMJERI PROVRTA SPOJKI

Tabela 2

	ES 1	ES 2	ES 3	ES 4	ES 5	ES 6	ES 7	ES 8	ES 9	ES 10	ES 11	ES 12	ES 13	ES 14	ES 15	ES 16
D_{max} pumpe	20	25	30	40	50	65	75	90	100	110	125	140	160	180	200	220
D_{max} motora	25	30	40	50	60	75	90	100	110	125	145	160	180	200	220	250