

# Seriya **TORRI FARO**



Pokretni uređaji s rasvjetom, kompletirani s generatorima serija SIRIO ili URBAN, 4 halogene svjetiljke i kolicima za ručno premještanje, opremljeni pneumatskim kotačima.

## Tehnički podaci

TORRI FARO		MODELI		
		ML EB 5,5 M	ML ED 5,5 M	HT 10 M
COD.		316.01	316.02	316.03
Model generatora Generator model		SIRIO 500 EBM	SIRIO 60 R EDM	URBAN 120 R EDM
Konsantna Snaga (P.R.P.) Continuous Power (P.R.P.)	KVA kW	4,2 3,7	6,0 5,4	10,0 8,8
cos φ			0,9	
Napon / Voltage	V		230	
Struja / Current	A	18,0	26,0	42,0
Broj faza / No. phases			F+N	
Broj okretaja / R.P.M.			3000	
Paljenje / Starting			Električno / Electric	
Svjetla / Lights	n°xW	4x500	4x500	4x1000/1500
Dimenzija otvorenog rasvjetnog tornja / Dimension of the lighting tower open:				
Dužina / Length	mm		1950	3530
Širina / Width	mm		2020	1450
Visina / Height	mm		5500	10000
Dimenzija zatvorenog rasvjetnog tornja / Dimension of the lighting tower closed:				
Dužina / Length	mm		2070	3530
Širina / Width	mm		850	1450
Visina / Height	mm		1200	1590
Težina / Weight	kg	179	213	525
<b>Tehnički podaci motora</b>				
Tip motora / Motor		Subaru	Lombardini / Ruggerini	
Model / Model		EX27	RY103	MD190
Gorivo / Fuel		Benzin / Gasoline	Diesel	
Radni obujem / Displacement	Lt	0,265	0,401	0,851
Ubrizgavanje / Injection		Karburator / Carburettor	Direktan / Direct	
Regulator brzine / Speed governor		Mehanički / Mechanical		
Kapacitet uljnog kartera Oil sump capacity	Lt	0,6	1,5	1,8
Hlađenje / Cooling		Zrak / Air		
Snaga motora / Engine power	kW	6,7	7,5	11,4
Kapacitet rezervoara / Tank capacity	Lt	6,1	5,0	20,0
Potrošnja pri 75% (P.R.P.) Consumption at 75% (P.R.P.)	l / h	1	1,8	2,7
Električni starter / Electric starting	V		12	
Ø Odvodnik / Discharger Ø	mm	14	28	65
<b>Tehnički podaci alternatora</b>				
Tip alternatora / Alternator		Sinhroni / Synchronous		
Model / Model		SP10	E1C10	E1C11
Broj polova / No. poles		2		
Konstantna snaga / Continuous power	KVA	4,2	6,0	12,0