

CENTRIFUGALNE PUMPE S DIESEL MOTORIMA IVECO,
VODOM HLADENI OD 60 Kw – 170 Kw



Motopompe Centrifughe - Diesel
Diesel Centrifugal Motorpumps

IVECO
MOTORS



Raffreddamento ad acqua
Water cooling





MOTOPOMPE DIESEL - **Centrifughe**
Centrifugal - DIESEL MOTORPUMP

IVECO
MOTORS

Prestazioni motopompa a: Motorpump performances at:	RPM 1750	Motore: Engine:	Raffreddato ad acqua Water cooling
--	-----------------	--------------------	---------------------------------------

TIPO MOTOPOMPA MOTORPUMP TYPE	CARATTERISTICHE MOTORE - ENGINE FEATURES					MODELLO POMPA PUMP MODEL	TIPO ACCOPPIAMENTO COUPLING TYPE		BOCCHIE POMPA PORTS PUMP		PORTATA DELIVERY L/1'	PREVALENZA HEAD MT	HP ASSORBITI ABSORBED
	MOTORE ENGINE	HP (H)	RPM	N° CILINDRI CYLINDERS	AVVIAMENTO STARTING		GIUNTO JOINT	DIRETTO DIRECT	DNa	DNm			
DC45MSA-M100CS	IVECO N45MSA	81	2300	4	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-M100CS	●		mm. 125	mm. 100	1000 1600 3000 4000	72 68 60 50	42 48 61 69
DC45MSA-M12531ACS	IVECO N45MSA	81	2300	4	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-M12531ACS	●		mm. 150	mm. 125	1400 2500 4000 6666	54 53 49 31	35 44 56 68
DC45MSA-M200GS	IVECO N45MSA	81	2300	4	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-M200GS	●		mm. 200	mm. 200	5000 6500 8000 10000	27,5 26,2 24 18	48 53 57,4 59
DC45MSA-M15031BCS	IVECO N45MSA	81	2300	4	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-M15031BCS	●		mm. 200	mm. 150	2200 4500 6500 8300	46 42 35 25	43 56 65 69
DC45MSA-M25017S	IVECO N45MSA	81	2300	4	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-M25017S	●		mm. 250	mm. 250	7000 10000 14000 17000	21,8 21 17,5 12	58 62 66 62
DC45MSA-P803A3S	IVECO N45MSA	81	2300	4	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-P803A3S	●		mm. 100	mm. 80	750 1250 1750 2300	117 110 98 76	40 50 58 65
DC45MSA-P804D3S	IVECO N45MSA	81	2300	4	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-P804D3S	●		mm. 100	mm. 80	750 1250 1750 2300	135 123 103 70	45 56,5 65 67
DC67MSA-M100BS	IVECO N67MSA	110	2500	6	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-M100BS	●		mm. 125	mm. 100	1000 2000 3000 4000	75 71 67 58	38 52 66 77
DC67MSA-M12540CCS	IVECO N67MSA	110	2500	6	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-M12540CCS	●		mm. 150	mm. 125	1400 2500 4000 6666	67 65 60 34	45 56 74 88
DC67MSA-M200ES	IVECO N67MSA	110	2500	6	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-M200ES	●		mm. 200	mm. 200	5000 6500 8000 10000	33 32 30 25	59 67 72 76
DC67MSA-P1002FS	IVECO N67MSA	110	2500	6	ELETTTRICO 12 V. ELECTRIC 12 V.	CS-P1002FS	●		mm. 125	mm. 100	1600 2500 3250 4000	95 86 75 64	55 69 77 82



MOTOPOMPE DIESEL - *Centrifughe*
Centrifugal - DIESEL MOTORPUMP



Prestazioni motopompa a: Motorpump performances at:	RPM 1750	Motore: Raffreddato ad acqua Engine: Water cooling
--	-----------------	---

TIPO MOTOPOMPA MOTORPUMP TYPE	CARATTERISTICHE MOTORE - ENGINE FEATURES					MODELLO POMPA PUMP MODEL	TIPO ACCOPIAMENTO COUPLING TYPE		BOCCHIE POMPA PORTS PUMP		PORTATA DELIVERY L/1'	PREVALENZA HEAD MT	HP ASSORBITI ABSORBED
	MOTORE ENGINE	HP (N)	RPM	N° CILINDRI CYLINDERS	AVVIAMENTO STARTING		GIUNTO JOINT	DIRETTO DIRECT	DNa	DNm			
DC45MSTD20-M100AS	IVECO N45MSTD20	128	2300	4	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M100AS	●		mm.	mm.	1000	86	48
											1600	84	58
											3000	77	76
									125	100	4000	67	92
DC45MSTD20-M12540BCS	IVECO N45MSTD20	128	2300	4	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M12540BCS	●		mm.	mm.	1400	75	53
											2500	73	68
											4000	68	85
									150	125	6666	46	106
DC45MSTD20-M15040CCS	IVECO N45MSTD20	128	2300	4	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M15040CCS	●		mm.	mm.	2200	66	61
											4500	62	88
											6500	52	101
									200	150	8333	34	106
DC45MSTD20-M200320BS	IVECO N45MSTD20	128	2300	4	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M200320BS	●		mm.	mm.	4166	48	84
											7500	43	106
											11600	33	108
									250	200	14000	26	104
DC45MSTD20-P1002DS	IVECO N45MSTD20	128	2300	4	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P1002DS	●		mm.	mm.	1600	114	65
											1500	106	86
											3250	97	98
									125	100	4000	86	109
DC67MSTD23-M12540ACS	IVECO N67MSTD23	163	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M12540ACS	●		mm.	mm.	1400	87	65
											2500	85	76
											4000	81	99
									150	125	6666	61	129
DC67MSTD23-P1002AS	IVECO N67MSTD23	163	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P1002AS	●		mm.	mm.	1600	135	79
											2500	126	104
											3250	118	123
									125	100	4000	108	136
DC67MSTD23-P1003FS	IVECO N67MSTD23	163	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P1003FS	●		mm.	mm.	1200	156	80
											2250	142	105
											3250	120	127
									125	100	4000	109	138
DC67MSTD23-P1502LRS	IVECO N67MSTD23	163	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P1502LRS	●		mm.	mm.	2000	110	80
											3000	107	100
											4000	100	120
									150	125	5000	78	134
DC60ENT-M15040ACS	IVECO N60ENT	230	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M15040ACS	●		mm.	mm.	2200	86	85
											5000	82	125
											7000	74	147
									200	150	9500	55	162
DC60ENT-M200360BS	IVECO N60ENT	230	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M200360BS	●		mm.	mm.	4166	62	108
											9100	58	147
											11600	52	168
									250	200	14000	45	174
DC60ENT-P1003AS	IVECO N60ENT	230	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P1003AS	●		mm.	mm.	1200	187	98
											2250	176	132
											3000	167	156
									125	100	4000	148	188
DC60ENT-P1502GRS	IVECO N60ENT	230	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P1502GRS	●		mm.	mm.	2000	133	104
											3000	130	128
											4000	124	153
									150	125	5000	110	174



MOTOPOMPE DIESEL - *Centrifughe*
Centrifugal - DIESEL MOTORPUMP

**IVECO
MOTORS**

Prestazioni motopompa a: Motorpump performances at:	RPM 2000	Motore: Raffreddato ad acqua Engine: Water cooling
--	-----------------	---

TIPO MOTOPOMPA MOTORPUMP TYPE	CARATTERISTICHE MOTORE - ENGINE FEATURES					MODELLO POMPA PUMP MODEL	TIPO ACCOPIAMENTO COUPLING TYPE		BOCCHIE POMPA PORTS PUMP		PORTATA DELIVERY L/1'	PREVALENZA HEAD MT	HP ASSORBITI ABSORBED
	MOTORE ENGINE	HP (N)	RPM	N° CILINDRI CYLINDERS	AVVIAMENTO STARTING		GIUNTO JOINT	DIRETTO DIRECT	DNa	DNm			
DC45MSA-M100DS	IVECO N45MSA	81	2300	4	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M100DS	●		mm.	mm.	1200	71	49
									125	100	2000	68	56
											3000	65	65
											4000	59	68
DC45MSA-M1253CCS	IVECO N45MSA	81	2300	4	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M1253CCS	●		mm.	mm.	1400	54	36
									150	125	2500	52	48
											4000	48	56
											6666	22	63
DC67MSA-M100CS	IVECO N67MSA	110	2500	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M100CS	●		mm.	mm.	1000	93	60
									125	100	1600	89	69
											3000	81	87
											4500	65	102
DC67MSA-M12531ACS	IVECO N67MSA	110	2500	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M12531ACS	●		mm.	mm.	1400	70	51
									150	125	3000	69	64
											5000	62	87
											6666	50	96
DC67MSA-P803A3S	IVECO N67MSA	110	2500	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P803A3S	●		mm.	mm.	1000	152	64
									100	80	1500	144	74
											2000	130	83
											2300	116	91
DC45MSTD20-M15031BCS	IVECO N45MSTD20	128	2300	4	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M15031BCS	●		mm.	mm.	2200	59	65
									200	150	4000	58	77
											8000	46	98
											10000	29	103
DC45MSTD20-P804D3S	IVECO N45MSTD20	128	2300	4	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P804D3S	●		mm.	mm.	1000	175	74
									100	80	1500	163	88
											2000	141	99
											2300	126	104
DC67MSTD23-M100AS	IVECO N67MSTD23	163	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M100AS	●		mm.	mm.	1200	112	71
									125	100	2000	107	86
											3000	102	103
											4500	86	136
DC67MSTD23-M12540BCS	IVECO N67MSTD23	163	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M12540BCS	●		mm.	mm.	1400	98	75
									150	125	3000	96	101
											4500	88	126
											6666	70	149
DC67MSTD23-M15031ACS	IVECO N67MSTD23	163	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M15031ACS	●		mm.	mm.	2200	68	70
									200	150	5000	67	100
											8300	55	125
											10800	35	135



MOTOPOMPE DIESEL - *Centrifughe*
Centrifugal - DIESEL MOTORPUMP

**IVECO
MOTORS**

Prestazioni motopompa a: Motorpump performances at:	RPM 2000	Motore: Raffreddato ad acqua Engine: Water cooling
--	-----------------	---

TIPO MOTOPOMPA MOTORPUMP TYPE	CARATTERISTICHE MOTORE - ENGINE FEATURES					MODELLO POMPA PUMP MODEL	TIPO ACCOPPIAMENTO COUPLING TYPE		BOCCHIE POMPA PORTS PUMP		PORTATA DELIVERY L/1'	PREVALENZA HEAD MT	HP ASSORBITI ABSORBED
	MOTORE ENGINE	HP (N)	RPM	N° CILINDRI CYLINDERS	AVVIAMENTO STARTING		GIUNTO JOINT	DIRETTO DIRECT	DNa	DNm			
DC67MSTD23-P804C3S	IVECO N67MST023	163	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P804C3S	●		mm. 100	mm. 80	1000 1250 1750 2300	179 174 159 131	76 84 96 108
DC67MSTD23-P1002ES	IVECO N67MST023	163	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P1002ES	●		mm. 125	mm. 100	1600 2750 3250 4000	141 129 128 119	92 129 135 142
DC60ENT-M12540ACS	IVECO N60ENT	230	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M12540ACS	●		mm. 150	mm. 125	1400 2500 4000 6666	113 111 109 87	94 109 138 175
DC60ENT-M15040BCS	IVECO N60ENT	230	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-M15040BCS	●		mm. 200	mm. 150	2200 4000 6500 8333	98 95 85 74	103 131 169 183
DC60ENT-P1002BS	IVECO N60ENT	230	2300	6	ELETTRICO 12 V. ELECTRIC 12 V.	CS-P1002BS	●		mm. 125	mm. 100	1600 2750 3500 4500	166 157 145 129	109 143 165 190